



According to the Regulation EC No. 1907/2006

## **CONSTANCE**

Date Prepared : Aug. 15, 2016 Revision Date :

Revision : 0 SDS No : GBF - 2154

## 1- IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY

#### 1.1- Product Identifier

Product Name CONSTANCE

## 1.2- Relevant identified uses of the substance advised against

Identified uses This paint can be used in all kinds of city and intercity roads, car parks and

other areas drawn.

Usage advised against It should not be applied on alkyd based cold road line paint.

### 1.3- Details of the supplier of the substance or mixture

Address SIGNATEKMA Boya ve Sinyalizasyon San.ve Tic. A.Ş.

Kurtuluş Caddesi No:23 Yazıbaşı – Torbalı / İzmir / Turkey

Telephone + 90 232 853 85 70 Fax + 90 232 853 73 79 E-mail info@signatekma.com.tr

## 1.4- Emergency telephone number

Signatekma 0 532 505 00 23

## 2- HAZARDS IDENTIFICATION

## 2.1- Classification of the substance:

#### According to the Regulation of EC 1272/2008 (CLP):

Flammable Liquid, Category 2, H225

Skin Irritation, Category 2, H315

Specific Target Organ Toxicity, Single Exposure, Category 3, H336

Reproductive System Toxicity, Category 2, H361

Specific Target Organ Toxicity, Repeated Exposure, Category 2, H373 (Central Nervous System)

#### 2.2- Label elements:

## According to the Regulation of EC 1272/2008 (CLP):

#### **Hazard Pictograms:**



Signal word Danger

#### **Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure

## **Precautinary statements**





According to the Regulation EC No. 1907/2006

## CONSTANCE

Date Prepared : Aug. 15, 2016 Revision Date : Revision : 0 SDS No : GBF - 2154

#### Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P233 Keep container tightly closed.

P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

#### Response

3

P303+P361+P35 IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P321 Specific treatment (see ... on this label).

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

P370+P378 In case of fire: water spray, alcohol-resistant foam, dry chemical or carbon

dioxide for extinction

P302+P352 IF ON SKIN: Wash with plenty of soap and water

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

**Disposal** 

P501 Dispose of contents/containers to the local regulations.

#### 2.3- Other Hazards:

Not applicable

## 3- COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2- Substance

Chemical name	EC No.	CAS No.	%	Classification
Toluene	203-625-9	108-88-3	10 ≤ X < 25	Flam. Liq2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373
Ethyl Acetate	205-500-4	141-78-6	2,5 ≤ X < 10	Flam. Liq2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of H-statements: see section 16.





According to the Regulation EC No. 1907/2006

## CONSTANCE

Date Prepared : Aug. 15, 2016 Revision Date :-

Revision : 0 SDS No : GBF - 2154

## 4- FIRST AID MEASURES

## 4.1- Description of first aid measures

#### General

Call a POISON CENTER or doctor/physician if you feel unwell.

#### Skin contact

Contact may cause moderate skin irritation during use. Avoid prolonged exposure to skin products. Wash the irritant area with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

#### Eye contact

Contact with product may cause severe eye irritation. In case of contact with dust, rinse affected eye with clean water for at least 15 minutes. If irritation occurs: Get medical advice/attention.

#### Inhalation

In case of inhalation, no significant effect is observed. As a precaution, take it outdoors and keep it in a comfortable position for easy breathing. If irritation persists, seek medical attention.

#### Ingestion

Under normal circumstances there is no chance of coming in. No significant irritation.

## 5- FIRE FIGHTING MEASURES

#### 5.1- General information

The product is classified as flammable. Flash point ≤ 21 °C

#### 5.2- Suitable Extinguishing Media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Never use water to extinguish.

### 5.3- Special hazards arising from the substance or mixture

No data available.

## 5.1- Special hazards arising from the substance or mixture

Wear full protective clothing including self-contained breathing apparatus for firefighting if necessary.

## 5.2- Special methods

Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Use explosion-proof electrical/ventilation/flammable/material.

## 6- ACCIDENTAL RELEASE MEASURES

### 6.1- Personal precautions, protective equipment, and emergency procedures

Avoid contact with eyes and skin of the product. Use personal protective equipment. Make sure of good ventilation. In case of insufficient ventilation wear suitable respiratory equipment.

#### 6.2- Environmental precautions

Collect contaminated/extinguishing water. Place spilled material in a container to dispose of non-combustible absorbent materials such as sand, earth, vermiculite, and diatomaceous earth in accordance with local regulations. (see section 13). Do not allow it to interfere with water, soil and sewage.





According to the Regulation EC No. 1907/2006

## CONSTANCE

Date Prepared : Aug. 15, 2016 Revision Date :-

Revision : 0 SDS No : GBF - 2154

## 6.3- Methods and materials for containment and cleaning up

This is a dangerous waste. Collect and packaging back for recycling or disposal.

#### 6.4- Reference to other sections

Information on safe handling is given in section 7. Information on personal protective equipment is given in section 8. Disposal information from chapter 13

### 7- HANDLING AND STORAGE

#### 7.1- Precautions for safe use

Ensure that the work area is well ventilated. Avoid long-term contact with your eyes and skin. Wash thoroughly with detergent after handling.

#### 7.2- Condition for safe storage, including any incompatibilities

Keep away from strong solvents and extreme heat. Store in a dry and well-ventilated enclosed area. Store in its original packaging. Take precautions against static discharges. The product can be electrostatically charged; Wear antistatic shoes and clothes. Protect from all kinds of fire and heat source, sunlight. Do not smoke.

### 7.3- Specific end use(s)

Road marking paint.

## 8- EXPOSURE CONTROLS, PERSONAL PROTECTION

# 8.1- Exposure Limit Values Control parameters

· OSHA:

Toluene (108-88-3)

TWA 200 ppm STEL 100 ppm

Ethyl Acetate (141-78-6)

TWA 5 ppm STEL 25 ppm

#### 8.2- Exposure controls









General Protection and Hygiene Measures

Keep the container tightly closed. Wash your hands at the end of the work and break. Do not eat or drink any food while using this product.

Respiratory protection

No respiratory protection is required. Use a mask according to EN 143 if

necessary.

Eye/Face protection

Use safety googles in accordance with EN 166 with side-shielded, which fit perfectly into areas where there is a high risk of splashing. It is advisable to

have a shower in the work area.

Hand protection

Use butyl rubber or nitrile gloves in accordance with EN 374. Protective cream can be used before starting work. Do not clean with cream after

coming into contact with paint.

Body protection

If necessary, use work clothes in accordance with EN 465 or EN 467 and

work shoes in accordance with EN 347 standards.





According to the Regulation EC No. 1907/2006

## CONSTANCE

Date Prepared : Aug. 15, 2016 Revision Date :-

Revision : 0 SDS No : GBF - 2154

### 8.3- Environmental exposure controls

The provisions of existing legislation for the protection of the environment must be fully implemented.

## 9- PHYSICAL AND CHEMICAL PROPERTIES

## 9.1- Information on basic physical and chemical properties:

Physical State Liquid

pH Not determined. Boiling point, °C Not determined

Flash point, °C ≤ 21 °C.

Vapor pressure (hPa) (20°C) below 110 kPa (1.10)

Density @ 20°C, gr/m³ > 1
Solubility in water @ 20°C insoluble.

9.2- Other Information:

Melting Point, ° C Not determined.

Decomposition Point, ° C Not determined.

Self-ignition Temperature, ° C Not determined.

## 10- STABILITY AND REACTIVITY

#### 10.1- Reactivity

The substance is stable under normal storage and handling conditions.

### 10.2- Possibility of hazardous reactions

Under normal circumstances, reactions that may occur are not dangerous.

#### 10.3- Conditions to avoid

Do not expose to incompatible materials.

## 10.4- Substances to avoid

Avoid strong acids and alkaline solutions that will damage the surface appearance of the material.

#### 10.5- Hazardous decomposition products

The thermal decomposition product may contain various liberated carbon oxides.

## 11- TOXICOLOGICAL INFORMATION

### 11.1- Information on toxicological effects

Acute toxicity No data available.

Components:

Toluene (108-88-3)

 Oral
 LD50: > 5000 mg/kg

 Inhalation
 LC50: 5320 ppm (8 h)

 Dermal
 LD50: > 5000 mg/kg

Ethyl Acetate (141-78-6)

 $\begin{array}{lll} \text{Oral} & \text{LD50: 5620 mg/kg} \\ \text{Inhalation} & \text{LC50:} > 18 \text{ mg/l (4 h)} \\ \text{Dermal} & \text{LD50:} > 20000 \text{ mg/kg} \\ \end{array}$ 

#### 11.2- Corrosion and irritation





According to the Regulation EC No. 1907/2006

## CONSTANCE

**Date Prepared** : Aug. 15, 2016 **Revision Date** 

Revision : GBF - 2154 SDS No

Serious eye damage/irritation No data available. Skin corrosion/irritation Causes skin irritation Skin sensitization No data available. No data available. Respiratory sensitization Respiratory tract irritation No data available

11.3- Chronic effects

Carcinogenicity Not listed in ACGIH, IARC or NTP.

11.4- Other Toxicity Effects

Mutagenicity No data available. Reproduction toxicity No data available **Epidemiology** No data available Teratogenicity No data available Specific Target Organ Toxicity -No data available

Single Exposure

Specific Target Organ Toxicity -

No data available

Repeated Exposure

## **ECOLOGICAL INFORMATION**

## 12.1- Toxicity

Product-related data is not available.

Components:

Toluene (108-88-3)

Acute fish toxicity LC50: 57,68 mg/l (96 h) Acute daphnia magna toxicity EC50: 11.5 mg/l (48 h) NOEC:> 400 mg/l (7 d) Acute algae toxicity

Ethyl Acetate (141-78-6)

Acute fish toxicity LC50: 900 mg/l (48 h) Acute daphnia magna toxicity EC50: 260 mg/l (48 h) Acute algae toxicity NOEC:> 100 mg/l (72 h)

### 12.2- Persistence and degradability

No data available.

### 12.3- Bioaccumulative potential

No data available.

#### 12.4- Mobility in soil

No data available.

### 12.5- Results of PBT and vPvB assessment

No data available.

#### 12.6- Other adverse effects

No data available.

## **DISPOSAL CONSIDERATIONS**

## 13.1- Waste treatment methods

Material may be hazardous and special handling may be required for disposal. Not given to sewer. Disposal in storage must comply with federal, state and local regulations.





According to the Regulation EC No. 1907/2006

## CONSTANCE

**Date Prepared** : Aug. 15, 2016 **Revision Date** 

Revision SDS No : GBF - 2154

## TRANSPORT INFORMATION

## Land transport (ADR / RID)

**14.1-** UN number UN1263 14.2- Proper UN transport name Paint 14.3- Transport hazard class(es) 3 14.4- Packing group Ш



14.6- Bulk transport according to Annex II of Not applicable.

MARPOL 73/78 and the IBC Code

5 L Limited quantity (ADR/RID Tank code (ADR/RID) **LGBF** FL Vehicle for tank carriage Tunnel code 2 (D/E) 33

Hazard identification no.

Orange plates 33 1263

## Sea transport (IMDG Code)

14.1- UN number UN1263 14.2- Proper UN transport name Paint 14.3- Transport hazard class (es) 3 14.4- Packing group Ш

14.5- Environmental hazards Not harmful to the environment.

14.6- Bulk transport according to Annex II of MARPOL 73/78 and the IBC Code

> Limited quantity (IMDG) LQ F-E EmS No (Fire) S-E N\*FS (Spill)


Air Transport (ICAO-IATA/DGR)

14.1- UN number UN1263 14.2- Proper UN transport name **Paint** 14.3- Transport hazard class (es) 3 14.4- Packing group

14.5- Environmental hazards Not harmful to the environment.

14.6- Bulk transport according to Annex II of Not applicable. MARPOL 73/78 and the IBC Code

#### **REGULATORY INFORMATION** 15-



- Regulation (EC) No 1907/2006, (REACH),
- Commission Regulation (EU) No 453/2010 amending Regulation (EC) No 1907/2006,

Not applicable.

Regulation (EC) No 1272/2008 (CLP),









According to the Regulation EC No. 1907/2006

## CONSTANCE

Date Prepared : Aug. 15, 2016 Revision Date : Revision : 0 SDS No : GBF - 2154

- Commission Directive 2006/15/EC,
- Commission Directive 2000/39/EC
- Council Directive 91/689/EEC.
- ADR European Agreement Concerning the International Carriage of Dangerous Goods by Road

## **16-OTHER INFORMATION**

## 16.1- The relevant H phrases (number and full text):

H225 Highly flammable liquid and vapour.H304 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

**H336** May cause drowsiness or dizziness.

**H361** Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure

## 16.2- Abbreviations and acronyms

ADR : European Agreement Concerning the Int. Carriage of Dangerous Goods by Road

CAS No : Chemical Abstract Service Index Number

EC No : European Commission Number

EC50 : Concentration which produces a certain effect under the conditions determined in 50% of

the organisms subjected to the test

IATA : International Air Transport Association ICAO : International Civil Aviation Organization

IMDG : International Maritime Code for Dangerous Goods

LC50 : Lethal Concentration 50% (Substance concentration should be in the air to kill 50% of the

test animals)

LD50 : Lethal Dose 50% (The amount of substance required to be dosed at a time to kill 50% of

test animals)

REACH: Regulation on the Registration, Evaluation, Authorisation and Restriction of Chemicals in

the European Union

STEL : Short Term Exposure Limit TWA : Time Weighted Average

## 16.3- Further Information:

This safety data sheet has been prepared in accordance with the information received from the product owner. The information in this document is based on the best available information. This information applies only to the specified substance/preparation.

The information given in this document does not constitute a guarantee/warranty for the product specifications and does not constitute a legally binding contract/contingent legal relationship feature. This document completes the technical documentation but can not be replaced. The information provided is based on our current knowledge of the product at the time of publication. Based on good goodness.

We do not accept responsibility for the product and information provided for similar materials not manufactured or supplied by SIGNATEKMA Boya ve Sinyalizasyon San. ve Tic. A.Ş.