



TECHNICAL DATA SHEET



SIGNATUBE

SPRAY LINE PAINT

- Our "Signatube" brand road marking spray paint is acrylic-based, fast-drying, high hiding, and yellowing resistance, forming a hard and flexible film.
- This paint is the first in Turkey and can be applied perpendicular to the ground.
- It is used in determining walking paths in places such as factories, sites, gas stations, determining parking areas, and designing playgrounds in schools.
- It can be applied by ALT-ST, ALT-ST 1, ALT-ST 2, or manually.
- Thanks to this feature, it provides practicality to the product in terms of use.
- Drying occurs when the solvent in the paint evaporates.

PRODUCT INFORMATION

- Class: Acrylic resin based spray road marking paint.
- Application Method: ALT-ST, ALT-ST 1, ALT-ST 2
- Product Name: Signatube

APPLICATION INFORMATION

Surface Preparation and Application Information:

Before the application, the area should be dry and away from dust, grease, and other dirt.

Use glove and mask during the application.

Drying Time: 15 min. (23 °C and % 49 Humidity)

Max. Humidity: % 80

PRODUCT CONSUMPTION AMOUNTS

Paint	4-5 m ² /tin
-------	-------------------------

Note: The values in the table are theoretical values. Consumption amount can be changed according to the surface and weather conditions.

PHYSICAL PROPERTIES

- Color: White
- Viscosity: 20 "± 5 (DIN4) 20 ° C
- Density: 1,50 g / ml. ± 0,1
- Luminance factor: LF7 / β ≥ 0,85
- Hiding power: At least %95

RAL 9016	RAL 5015	RAL 1023	RAL 6001
RAL 9017	RAL 2004	RAL 3020	RAL 7040

RAL kataloğundan seçilen renk kodlarına göre istenilen renklerde üretilmektedir. | It can be produced according to the color codes selected from the RAL catalogue.

PACKAGING AND STORAGE CONDITION

• **Packaging:** 500 ml, 750 ml

• **Storage:** Store at closed areas, and get away from fire sources.