



TECHNICAL DATA SHEET



PRIMER

ACRYLIC BASED PRIMER

- It is a one-component, solvent-based, acrylic-based transparent primer with excellent adhesion.
- Thanks to its high strength, it maintains its adhesion power and film thickness for a long time under heavy traffic.
- Its UV resistance and chemical resistance is very high.
- Thanks to its high adhesion, it is applied on smooth floors, as a primer between the floor and the paint, and on the paint where protection and shine is desired.
- Since it dries quickly and hardens, the application area is opened to traffic within 15 minutes.

PRODUCT INFORMATION

- Class: Transparent acrylic primer paint.
- Application Method: It is recommended to apply by spraying on the road surface with automatic application equipment. If required, it can be applied with a brush or a roller.
- Product Name: Primer

APPLICATION INFORMATION

- Before the application, it must be ensured that the application surface is dry, free of dust, oil and other dirt. It should not be applied on wet ground.
- **Ground Temperature:** The surface temperature of the road must be above 15 ° C.
- **Maximum Humidity:** %80
- **Dry Time:** 15 min.(17 °C and % 49 Humidity)

PHYSICAL PROPERTIES

- Color: Transparent
- Viscosity: 45 ± 10 KU (23°C±2)
- Density: 0,9 g / ml. ± 0,1

PACKAGING AND STORAGE CONDITION

- Packaging: 15 kg/Can
- At proper storage conditions, shelf life is 1 year.
- Store at closed areas, and get away from fire sources.