



According to the Regulation REACH EC 2020/878

# SIGNALINE

Date Prepared : Aug. 15, 20	23	Revision Date	: 09.01.2025
Revision : 0		SDS No	: GBF – 2151
1- IDENTIFICATION O	F THE SUBSTANCE AND OF THE C	COMPANY	
1.1- Product Identifier			
Product Name	SIGNALINE		
1.2- Relevant identified use	s of the substance advised against		
Identified uses	This paint is used in all kinds of city and inter areas are drawn	city road, parking	lot and other
Usage advised against	No data available		
1.3- Details of the supplier	of the substance or mixture		
Address	SIGNATEKMA Boya ve Sinyalizasyon San.v	e Tic. A.Ş.	
	Bahçelievler Mah. Bağımsızlık Caddesi No:2	3 Yazıbaşı –	
	Torbalı / İzmir / Turkey	,	
Telephone	+ 90 232 853 85 70		
Fax	+ 90 232 853 73 79		
E-mail	info@signatekma.com.tr		
	<u> </u>		

### 1.4- Emergency telephone number

Signatekma	0 532 505 00 23
Oignatekina	0 002 000 00 20

# 2- HAZARDS IDENTIFICATION

## 2.1- Classification of the substance:

According to the Regulation of EC 1272/2008 (CLP): Flammable Liquid, Category 2, H225 Skin Irritation, Category 2, H315 Specific Target Organ Toxicity, Single Exposure, Category 3, H336 Reproductive System Toxicity, Category 2, H361 Specific Target Organ Toxicity, Repeated Exposure, Category 2, H373 (Central Nervous System)

## 2.2- Label elements:

According to the Regulation of EC 1272/2008 (CLP): Hazard Pictograms:



Signal word Danger Hazard statements

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness
- H361 Suspected of damaging fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure

**Precautinary statements** 

Prevention



According to the Regulation REACH EC 2020/878



# SIGNALINE

	Date Prepared Revision	: Aug. 15, 2 : 0	2023	Revision Date SDS No	: 09.01.2025 : GBF – 2151	
		P210	Keep away from heat/sparks/open flames/hot	surfaces No sm	oking.	
		P233	Keep container tightly closed.			
		P241	Use explosion-proof electrical/ventilating/lighti	ng//equipment.		
		P242	Use only non-sparking tools.			
P243			Take precautionary measures against static di	ischarge.		
		P264	Wash hands thoroughly after handling.			
		P271	Use only outdoors or in a well-ventilated area.			
		P280	Wear protective gloves/protective clothing/eye	protection/face pr	rotection.	
	Resp	onse				
	•	P361+P353	IF ON SKIN (or hair): Remove/Take off immed clothing. – Rinse skin with water/shower.	liately all contamir	nated	
	F	P304+P340	IF INHALED: Remove victim to fresh air and k comfortable for breathing.	eep at rest in a po	osition	
	F	P308+P313	IF exposed or concerned: Get medical advice/	attention.		
P312			Call a POISON CENTER or doctor/physician if you feel unwell.			
P321			Specific treatment (see on this label).			
	F	P332+P313	If skin irritation occurs: Get medical advice/atte			
		P362	Take off contaminated clothing and wash befo			
	F	P370+P378	In case of fire: Use water spray, alcohol-resista carbon dioxide for extinction	ant foam, dry cher	mical or	
	F	P302+P352	IF ON SKIN: Wash with plenty of soap and wa			
	F	P333+P313	If skin irritation or rash occurs: Get medical ad	vice/attention.		
	Stora	ge				
	F	P403+P233	Store in a well-ventilated place. Keep contained	r tightly closed.		
	F	P403+P235	Store in a well-ventilated place. Keep cool.			
		P405	Store locked up.			
	Dispo	osal				
		P501	Dispose of contents/containers to the local reg	julations.		
	2.3- Other Haz	ards:				

Not applicable

# **3- COMPOSITION/INFORMATION ON INGREDIENTS**

## 3.2- Substance

Chemical name	EC No.	CAS No.	%	Classification
Toluene	203-625-9	108-88-3	10 ≤ X < 25	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 2, H373 Repr. 2, H361
Ethyl Acetate	205-500-4	141-78-6	2,5 ≤ X < 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of H-statements: see section 16.



According to the Regulation REACH EC 2020/878



# SIGNALINE

Revision Date	: 09.01.2025
SDS No	: GBF – 2151

## 4- FIRST AID MEASURES

## 4.1- Description of first aid measures

### General

Call a POISON CENTER or doctor/physician if you feel unwell.

## Skin contact

Contact may cause moderate skin irritation during use. Avoid prolonged exposure to skin products. Wash the irritant area with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

### Eye contact

Contact with product may cause severe eye irritation. In case of contact with liquid, rinse affected eye with clean water for at least 15 minutes. If irritation occurs: Get medical advice/attention.

### Inhalation

In case of inhalation, no significant effect is observed. As a precaution, remove the victim to fresh air and hold him in a comfortable position for easy breathing. If irritation persists, seek medical attention.

### Ingestion

Under normal circumstances there is no chance of coming in. No significant irritation.

# **5- FIRE FIGHTING MEASURES**

## 5.1- General information

The product is classified as flammable. Flash point ≤ 21 °C

## 5.2- Suitable Extinguishing Media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Never use water to extinguish.

**5.3- Special hazards arising from the substance or mixture** No data available.

## 5.1- Special hazards arising from the substance or mixture

Wear full protective clothing including self-contained breathing apparatus for firefighting if necessary.

#### 5.2- Special methods

Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Use explosion-proof electrical/ventilation/flammable/material.

# 6- ACCIDENTAL RELEASE MEASURES

## 6.1- Personal precautions, protective equipment, and emergency procedures

Avoid contact with eyes and skin of the product. Use personal protective equipment. Make sure of good ventilation. In case of insufficient ventilation wear suitable respiratory equipment.

## 6.2- Environmental precautions

Collect contaminated/extinguishing water. Place spilled material in a container to dispose of noncombustible absorbent materials such as sand, earth, vermiculite, and diatomaceous earth in accordance with local regulations. (see section 13). Do not allow it to interfere with water, soil and sewage.





According to the Regulation REACH EC 2020/878

# SIGNALINE

Date Prepared	: Aug. 15, 2023	Revision Date	: 09.01.2025
Revision	: 0	SDS No	: GBF – 2151

## 6.3- Methods and materials for containment and cleaning up

This is a dangerous waste. Collect and packaging back for recycling or disposal.

## 6.4- Reference to other sections

Information on safe handling is given in section 7. Information on personal protective equipment is given in section 8. Disposal information from chapter 13

# 7- HANDLING AND STORAGE

## 7.1- Precautions for safe use

Ensure that the work area is well ventilated. Avoid long-term contact with your eyes and skin. Wash thoroughly with detergent after handling.

## 7.2- Condition for safe storage, including any incompatibilities

Keep away from strong solvents and extreme heat. Store in a dry and well-ventilated enclosed area. Store in its original packaging. Take precautions against static discharges. The product can be electrostatically charged; Wear antistatic shoes and clothes. Protect from all kinds of fire and heat source, sunlight. Do not smoke.

### 7.3- Specific end use(s)

Road marking paint.

# 8- EXPOSURE CONTROLS, PERSONAL PROTECTION

# 8.1- Exposure Limit Values

## **Control parameters**

• OSHA:

Toluene (108-88-3)	
TWA	200 ppm
STEL	100 ppm
Ethyl Acetate (141-78-6)	
TWA	5 ppm
STEL	25 ppm

## 8.2- Exposure controls



General Protection and Hygiene Measures	Keep the container tightly closed. Wash your hands at the end of the work and break. Do not eat or drink any food while using this product.
Respiratory protection	No respiratory protection is required. Use a mask according to EN 143 if necessary.
Eye/Face protection	Use safety googles in accordance with EN 166 with side-shielded, which fit perfectly into areas where there is a high risk of splashing. It is advisable to have a shower in the work area.
Hand protection	Use butyl rubber or nitrile gloves in accordance with EN 374. Protective cream can be used before starting work. Do not clean with cream after coming into contact with paint.
Body protection	If necessary, use work clothes in accordance with EN 465 or EN 467 and work shoes in accordance with EN 347 standards.



According to the Regulation REACH EC 2020/878



# SIGNALINE

Date Prepared	: Aug. 15, 2023	Revision Date	: 09.01.2025
Revision	: 0	SDS No	: GBF – 2151

#### 8.3- Environmental exposure controls

The provisions of existing legislation for the protection of the environment must be fully implemented.

## 9- PHYSICAL AND CHEMICAL PROPERTIES

### 9.1- Information on basic physical and chemical properties:

Physical State pH Boiling point, °C Flash point, °C Vapor pressure (hPa) (20°C) Density @ 20°C, gr/m<sup>3</sup> Solubility in water @ 20°C

## 9.2- Other Information:

Melting Point, ° C Decomposition Point, ° C Self-ignition Temperature, ° C

## 10- STABILITY AND REACTIVITY

#### 10.1- Reactivity

The substance is stable under normal storage and handling conditions.

#### 10.2- Possibility of hazardous reactions

Under normal circumstances, reactions that may occur are not dangerous.

#### 10.3- Conditions to avoid

Do not expose to incompatible materials.

#### 10.4- Substances to avoid

Avoid strong acids and alkaline solutions that will damage the surface appearance of the material.

#### 10.5- Hazardous decomposition products

The thermal decomposition product may contain various liberated carbon oxides.

## 11- TOXICOLOGICAL INFORMATION

## 11.1- Information on toxicological effects

Acute toxicity	No data available.
Components:	
Toluene (108-88-3)	
Oral	LD50: > 5000 mg/kg
Inhalation	LC50: 5320 ppm (8 h)
Dermal	LD50: > 5000 mg/kg
Ethyl Acetate (141-78-6)	
Oral	LD50: 5620 mg/kg
Inhalation	LC50: > 18 mg/l (4 h)
Dermal	LD50: > 20000 mg/kg
11.2- Corrosion and irritation	

Serious eye damage/irritation

No data available.

Liquid Not determined. 133.20 °C. 33.42 °C. below 110 kPa (1.10) > 1 insoluble.

Not determined. Not determined. Not determined.



According to the Regulation REACH EC 2020/878



# SIGNALINE

_							
	ate Prepared	: Aug. 15, 2023			Revision Date	: 09.01.2025	
R	evision	:0			SDS No	: GBF – 2151	
		osion/irritation		Causes skin irritation			
	Skin sen			Causes skin irritation.			
	•	ory sensitization		No data available.			
Respiratory tract irritation			May cause damage to organs repeated exposure.	through prolonge	d or		
11	.3- Chronic	effects					
	Carcinog	enicity		Not listed in ACGIH, IARC or I	NTP.		
11	.4- Other To	xicity Effects					
	Mutagen	icity		No data available.			
Reproduction toxicity			Suspected of damaging fertility	/ or the unborn ch	ild.		
	Epidemic	ology		No data available			
	Teratoge	nicity		No data available			
	Specific Single Ex	Target Organ To: xposure	xicity -	May cause drowsiness or dizz	iness		
		Target Organ To d Exposure	xicity -	May cause damage to organs repeated exposure	through prolonged	d or	
_	Repeated			repeated exposure			

## 12- ECOLOGICAL INFORMATION

#### 12.1-Toxicity

Product-related data is not available. Components: Toluene (108-88-3) Acute fish toxicity Acute daphnia magna toxicity EC50: 57,68 mg/l (96 h) Acute daphnia magna toxicity EC50: 11.5 mg/l (48 h) Acute algae toxicity Ethyl Acetate (141-78-6) Acute fish toxicity Acute daphnia magna toxicity EC50: 900 mg/l (48 h) Acute algae toxicity NOEC:> 100 mg/l (72 h)

- 12.2- Persistence and degradability No data available.
- 12.3- Bioaccumulative potential

No data available.

- 12.4- Mobility in soil No data available.
- 12.5- Results of PBT and vPvB assessment No data available.
- 12.6- Other adverse effects

No data available.

## 13- DISPOSAL CONSIDERATIONS

#### 13.1- Waste treatment methods

Material may be hazardous and special handling may be required for disposal. Not given to sewer. Disposal in storage must comply with federal, state and local regulations.

SIGNATEKMA

According to the Regulation REACH EC 2020/878



# SIGNALINE

Date Prepared : Aug. 15, 2023 Revision : 0	Revision SDS No	
14- TRANSPORT INFORMAT	ION	
Land transport (ADR / RID)		
14.1- UN number	UN1263	•
14.2- Proper UN transport name	Paint	
14.3- Transport hazard class(es)	3	
14.4- Packing group	III	3
14.5- Environmental hazards	Not harmful to the environment.	

LGBF

2 (D/E)

33

1263

UN1263

Paint

3

FL

33

14.6- Bulk transport according to Annex II of MARPOL 73/78 and the IBC Code Limited quantity (ADR/RID Tank code (ADR/RID) Vehicle for tanker Tunnel ode Hazard identification no. Orange plates

Sea transport (IMDG Code)

14.2- Proper UN transport name

14.3- Transport hazard class (es)

14.1- UN number

Not applicable. 5 L



14.4- Packing group	III
14.5- Environmental hazards	Not harmful to the environment.
14.6- Bulk transport according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
Limited quantity (IMDG)	LQ
EmS No (Fire)	F-E
N*FS (Spill)	S-E
Air Transport (ICAO-IATA/DGR)	
14.1- UN number	UN1263
14.2- Proper UN transport name	Paint
14.3- Transport hazard class (es)	3
14.4- Packing group	111
14.5- Environmental hazards	Not harmful to the environment.
<b>14.6-</b> Bulk transport according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.



**SIGNATEKMA** 

According to the Regulation REACH EC 2020/878



# **SIGNALINE**

# 15- REGULATORY INFORMATION

## 15.1- Safety, health and environmental regulations specific for the substance or mixture

- Regulation (EC) No 1907/2006, (REACH),
- Commission Regulation (EU) No 453/2010 amending Regulation (EC) No 1907/2006,
- Regulation (EC) No 1272/2008 (CLP),
- Commission Directive 2006/15/EC,
- Commission Directive 2000/39/EC
- Council Directive 91/689/EEC,
- ADR European Agreement Concerning the International Carriage of Dangerous Goods by Road

## **16- OTHER INFORMATION**

16.1- The relevant H phrases (number and full text):

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361 Suspected of damaging fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure

#### 16.2- Abbreviations and acronyms

ADR : European Agreement Concerning the Int. Carriage of Dangerous Goods by Road

- CAS No : Chemical Abstract Service Index Number
- EC No : European Commission Number
- EC50 : Concentration which produces a certain effect under the conditions determined in 50% of the organisms subjected to the test
- IATA : International Air Transport Association
- ICAO : International Civil Aviation Organization
- IMDG : International Maritime Code for Dangerous Goods
- LC50 : Lethal Concentration 50% (Substance concentration should be in the air to kill 50% of the test animals)
- LD50 : Lethal Dose 50% (The amount of substance required to be dosed at a time to kill 50% of test animals)
- REACH : Regulation on the Registration, Evaluation, Authorisation and Restriction of Chemicals in the European Union
- STEL : Short Term Exposure Limit
- TWA : Time Weighted Average

#### **16.3-** Further Information:

This safety data sheet has been prepared in accordance with the information received from the product owner. The information in this document is based on the best available information. This information applies only to the specified substance/preparation.

The information given in this document does not constitute a guarantee/warranty for the product specifications and does not constitute a legally binding contract/contingent legal relationship feature. This document completes the technical documentation but can not be replaced. The information provided is based on our current knowledge of the product at the time of publication. Based on good goodness.

We do not accept responsibility for the product and information provided for similar materials not manufactured or supplied by SIGNATEKMA Boya ve Sinyalizasyon San. ve Tic. A.Ş.